

**Part Three** 

## **Connect a Tablet to MacroGenerator**



for any information or support please do not hesitate to contact us

support@macrogenerator.net

or visit

www.macrogenerator.net

## **Chapter 5 - Configuration for connection Tablet**

MG offers the ability to connect to itself for up to 99 devices, Tablet, Smartphone or PC, iOS, Android or Windows Phone, the important thing is that they are within the same network, and it is very important that the Ports of Pc are tested and is allow to MG Firewall so that it can make available to all devices, its Server service.

At this open the control panel and check the small box "Connect Tablet to MG"



At the first use of this function you will be prompted to allow to the Firewall for MG

Windows Sec	urity Alert		×
Windo	ws Firewal	I has blocked some features of this app	
Windows Firewall h networks.	as blocked som	e features of Macro Generator on all public and private	
The	Name:	Macro Generator	
	Publisher:	Walter Iermano	
	Path:	C:\program files\macrogenerator\macrogenerator.exe	
Allow Macro Gener	ator to commun vorks, such as m	icate on these networks: ny home or work network	
Public netwo because the	orks, such as the se networks off	ose in airports and coffee shops (not recommended ten have little or no security)	
What are the risks	of allowing an a	pp through a firewall?	
		Allow access Cance	4

By checking the two little boxes highlighted in red, say to the firewall that MG has our permission to connect a device to our PC, unless you authorize the firewall, you may not use the connection with the Tablet PC.

- Tablet Connection	т	ablet Settings			₽●⊗
IP 192.168.1.7	Socket Port	8080 🖨	Socket Test	Socket Test Ok!	
	Server Port	80 🜻	Server Test	Server Test Ok!	
Mail Mail					
On Tablet					
Show Transport Keys	Height 40 븆	Width Spa 60 🖨 5	ace		
Macros On Tablet Rows Columns	Height	Width Spa	ace		
Tablet GUI	Font Si	ze Increase			
Background Color	3	Deleta	e blanks		
:					
		_			
Connect and Show Link Conr Address A	ect and Send Link ddress via Mail	Connect an Address	d Save Link As File	Cancel	

At this point the Tablet Settings window, it is automatically made the Test Socket Server and, if there are errors, the buttons are red and not green.

If the "Test Socket" button is red you need to change the number of Socket, increasing the value of a click and Test Socket, if the button turns green ok, otherwise continue until it turns green

The same should be done for Test Server.

In most cases the values for the Socket 8080 and 80 for the port are always available.

Once the tests have been successful, we look at the various settings,

We have all the options that modify the look and feel of the buttons on the Tablet, we can also set whether the Transport Keys or not, we can change the size of the buttons, font, and background color

The field value of the IP interface is the value of the network with which the PC is connected to the router, and normally begins with 192.168.1. \* Or 192.168.0. \*, Where "\*" can vary from 2 to 254,

Enter your email if you want to use the "Connect and send Link Address via mail", so will be sent an email to the device you must connect to the PC, you will receive an email with a direct link by clicking on the link and the device opens the browser and connects directly to your PC

Enter a path to a file, if you want to use the "Connect and Save Link Address As File", in this case, a text file is saved with the link for the browser, so we can transfer the file to a USB stick or Network.

The last option is to click on "Connect and Show Link Address" once you click on this message appears on the screen



Now depending on the type of Tablet operating system we are going to install the application from the store, then store or seek on the "MacroGenerator" application, or open the Information menu



And you will see this screen



With all the links necessary to go on the store, or by clicking on the symbol of the appropriate store will open on QR Code that once scanned with the Tablet will open the application directly from the Store





We install the application on your tablet, and text box insert the IP address and port as it appears on your PC

			_						
IP Add Port A	IP Address = 192.168.1.7 Port Address = 80 Connect to MacroGenerator Pc Connect Via Browser		- Tablet Connection IP 192.168.1.7	- Tablet Connection IP 192.168.1.7 Socket Port Server Port			Socket Test Ok	k! d	
	-	+	,		1	2	3	Ø	
	*	/			4	5	6	0	
	(	)	=		7	8	9		

Then click on "Connect to MacroGenerator Pc" and the tablet will have this screen

From now we can run macros from the tablet

3-Way Color Correction	Color Balance	YUV Curve	Primary Color Correction	25	50	100	100	
Dissolve Auto in	Dissolve Auto Out	Color Clip Green		Color Clip Blue	Color Clip Yellow	Color Clip Gray	Color Clip Default	
Cut Single Track	Cut All Track	Layout 1	Layout 2	Disable Audio	Enable Audio	Parametric Equalizer	Panpot and Balance	
Stereo	Mono1	Mono2	Export Frame	Export H264	Export Wav	Export Blu- Ray	Export MPEG2 PAL DVD	
Export Default	Export Project	Batch Panel	Export	Сору	Cut	Paste	Alpha Custom Map	
Monotone	Sepia type 1	Chrominance	Blur	Old Movie	Soft Focus	Strobe Freeze	Mask	
् 📄		••		> >>		D P	۹ 🗖	

The macros that will appear on the tablet are all those macros that are in the container board in MG "Tablet"

Ţ,	۵ 🗠	MacroGer	MacroGenerator 1.0 (64 bit)Trial (2 remaining days)									
۲	Macro											
Commands 📀 Cycle 📷 Effects	Video T	imeline Au	idio Export	Various	Tablet							
	3-Way Color Correction	Color Balance	YUV Curve	Primary Color Correction	25	50	^	ce Comr				
	100	100	Dissolve Auto In	Auto Out	Color Clip Green	Color Clip Red		nand				
	Color Clip Blue	Color Clip Yellow	Colur Clip Gray	Color Clip Default	Cut Single Track	Cut All Track		Trans				
	Layout 1	Lay ut 2	Disable Audio	Enable Audio	Parametric Equalizer	Panpot and Balance		sport Key				
	Stereo	Mono1	Mono2	Export Frame	Export H264	Export Wav		S				
en-e	Export Blu- en 966,136	Export EDIUS	Export 8 Recognized	Export		F .	~					

The various changes applied to the macro and the favorite did not take effect immediately but you



Connect Tablet to

MG

have to reboot the server, and then disconnect the device using the check box

, And we will have the message of the closed connection



At this point if you want to reconnect all just repeat the click of